



NOTE:

1. COUPLINGS ARE ORIENTED 180° APART WITHIN ONE DEGREE. OTHER HOLE SIZES AND/OR LOCATIONS MUST BE SPECIFIED WHEN ORDERING.
2. THREADS INSIDE COUPLINGS ARE PROTECTED WITH LDPE PLUGS.
3. PLYWOOD COVER IS 1/2" NOMINAL THICKNESS, GRADE CC, WITH Ø7/16" BOLT HOLES. PLYWOOD THICKNESS RUNS UNDERSIZED; ACTUAL THICKNESS IS 15/32" +0/-1/32".
4. OPTIONAL COPPER GROUND LUG, DRAIN COUPLING AND/OR OPENING MUST BE SPECIFIED WHEN ORDERING.
5. FINISH-HOT DIP GALVANIZED PER ASTM A123.
6. LIGHT BASE HEIGHT IS ADJUSTABLE FROM 17 7/8" TO 29 1/2".
7. L867 ADJUSTABLE LIGHT BASE MUST BE EMBEDDED IN PORTLAND CEMENT CONCRETE TO MEET LOAD REQUIREMENTS OF FAA.

DWN: DOUG F.

DATE: 7/17/2017

SCALE: NTS

SHEET 1 OF 1

L-867B Ø16" ADJUSTABLE LIGHT BASE,
29 1/2" MAX HEIGHT, WITH COUPLINGS



MILLERBERND

622 6TH ST. SO.
WINSTED, MN
55395

167ACC295PCC